



# Pladelageret

Birkekrydsfiner. Film / Film, WBP-limet. 120 gr. mørkebrun fenolfilm									
Tykkelse	6,5 mm	9 mm	12 mm	15 mm	18 mm	21 mm	27 mm	30 mm	40 mm
	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500	1500 x 3000	1250 x 2500	1500 x 3000
		1500 x 3000	1500 x 3000	1500 x 3000	1500 x 3000	1500 x 3000		1500 x 3000	
						1500 x 3660			
Birkekrydsfiner. Wire/Film, WBP-limet. 120 gr. mørkebrun fenolfilm.									
Tykkelse	9 mm	12 mm	15 mm	18 mm	21 mm	27 mm	30 mm		
	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500		
	1500 x 3000	1500 x 3000	1500 x 3000	1500 x 3000	1500 x 3000	1500 x 3000	1500 x 3000		
Birkekrydsfiner. Wire/Film, WBP-limet. 220 gr. mørkebrun fenolfilm.									
Tykkelse	27 mm.								
	1250 x 2500								
Birkekrydsfiner. MAXI Wire/Film, WBP-limet. 220 gr. mørkebrun fenolfilm.									
Tykkelse	9 mm	12 mm	15 mm	18 mm	21 mm				
	1810 x 3500	1810 x 2900	1700 x 2800	1700 x 3800	2100 x 3300				
	1810 x 3600		1700 x 3800	2100 x 3750	2100 x 3600				
	1810 x 3800		2100 x 4350	2100 x 4350	2100 x 3900				
					2200 x 4400				
Birkekrydsfiner. Maxi Film/Film, WBP-limet. 220 gr. mørkebrun fenolfilm.									
Tykkelse	21 mm								
	2200 x 4400								
Birkekrydsfiner. Wire/Film, WBP limet. 700 gr. floor									
Tykkelse	18 mm								
	1525 x 3050								



# Pladelageret

Birkekrydsfiner. Film/Film lys grå (Ral 7040), WBP-limet. 0,2 mm. termoplast									
Tykkelse	6,5 mm	12 mm							
	1250 x 2500	1250 x 2500							
	1525 x 3660								
Birkekrydsfiner. Film/Film hvid, WBP-limet. 0,2 mm. termoplast									
Tykkelse	12 mm	15 mm	18 mm	21 mm					
	1500 x 3000	1500 x 3000	1500 x 3000	1500 x 3000					
Birkekrydsfiner. S/WG, WBP-limet og pudset overflade.									
Tykkelse	9 mm	12 mm	15 mm	18 mm	21 mm				
	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500	1250 x 2500				
Birkekrydsfiner. S/BB, WBP-limet og pudset overflade.									
Tykkelse	6,5 mm	15 mm							
	1250 x 2500	1250 x 2500							
Birkefiner BB/BB, WBP-limet og pudset overflade									
Tykkelse	18 mm	21 mm							
	1250 x 2500	1250 x 2500							
Birkekrydsfiner. BB/CP, WBP-limet og pudset overflade.									
Tykkelse	9 mm	12 mm	18 mm	21 mm					
	1250 x 2500	1250 x 2500	1250 x 250	1250 x 2500					
	2500 x 1250								
Spruce krydsfiner II/III, WBP-limet.									
Tykkelse	18 mm	21 mm							
	1250 x 2500	1250 x 2500							



# Pladelageret

Plankeværksplade MCX, WBP-limet									
Tykkelse	12 mm	15 mm	18 mm	21 mm					
	1220 x 2440	1220 x 2440	1220 x 2440	1220 x 2440					
Okoume B/BB, WBP-limet									
Tykkelse	4 mm	6 mm	8 mm.	10 mm.	12 mm.	15 mm.	18 mm.		
	2500 x 1220	2500 x 1220	2500 x 1220	2500 x 1220	2500 x 1220	2500 x 1220	2500 x 1220		
Mahognifiner på okoumeplader. Tykkelsestolerance +/- 0,8 mm.									
Tykkelse	7 mm	10 mm	14 mm						
	1220 x 2300	1220 x 2300	1220 x 2300						
Teakfiner på okoumeplader. Tykkelsestolerance +/- 0,8 mm.									
Tykkelse	7 mm	10 mm	14 mm						
	1220 x 2300	1220 x 2300	1220 x 2300						